

L SERIES RECOVERY UNIT

Mini Recovery Unit VRR12L-R32

- Suitable for 1234yf and r32 refrigerant
- One key operation, easy to use
- No spark



• *Chinese patent*

Special Designed
Power Button



VRR12LOS-R32

- Suitable for 1234yf and r32 refrigerant
- Purification and recycling of the refrigerants



Specifications

Model	VRR12L-R32				VRR12LOS-R32			
Refrigerants	Category III: R12,R134a,R401C,R500,1234yf							
	Category IV: R22,R401A, R401B, R402B, R407C, R407D, R408A,R409A,R411A R411B,R412A,R502,R509							
	Category V: R402A,R404A,R407A,R407B,R410A,R507,R32							
	Power Supply	220V-240V~/50-60Hz	115V~/60Hz		220V-240V~/50-60Hz	115V~/60Hz		115V~/60Hz
	Motor	3/4 HP	3/4 HP		3/4 HP	3/4 HP		3/4 HP
Motor Speed	1450rpm/1750rpm	1750rpm		1450rpm/1750rpm	1750rpm		1750rpm	
Maximal Current Draw	4A		8A		4A		8A	
Compressor	Oil-less, Air-cooled, Piston style							
Automatic safety Shut-Off								
Recovery Rate (kg/min)	Category III	Category IV	Category V	Category III	Category IV	Category V	Category V	
	0.20	0.25	0.25	0.20	0.25	0.25	0.25	
	1.60	1.80	2.20	1.60	1.80	2.20	2.20	
	Push/pull	4.60	5.60	6.30	4.60	5.60	6.30	
Operating Temperature	0°C~40°C							
Dimensions	450×250×355mm							
Weight	13.0 Kg				14.2 Kg			

L SERIES RECOVERY UNIT

Mini Recovery Unit VRR24L-R32

- Suitable for 1234yf and R32 refrigerant
- One key operation, easy to use
- No spark



• *Chinese patent*

Special Designed
Power Button



VRR24LOS-R32

- Suitable for 1234yf and r32 refrigerant
- Purification and recycling of the refrigerants



Specifications

Model	VRR24L-R32				VRR24LOS-R32			
Refrigerants	Category III: R12, R134a, R401C, R500, 1234yf							
	Category IV: R22, R401A, R407B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509							
	Category V: R402A, R404A, R407A, R407B, R410A, R507, R32							
	Power Supply	220V~240V~/50-60Hz	115V~/60Hz	1 HP	1 HP	220V~240V~/50-60Hz	115V~/60Hz	1 HP
Motor		1 HP	1 HP	1 HP	1 HP	1 HP	1 HP	1 HP
Motor Speed		1450rpm/1750rpm	1750rpm	1750rpm	1450rpm/1750rpm	1750rpm	1750rpm	1750rpm
Maximal Current Draw		5A	10A	5A	5A	10A	5A	10A
Compressor	Oil-less, Air-cooled, Piston style							
Automatic safety Shut-Off								
Recovery Rate (Kg/min)	Category III	Category IV	Category V	Category III	Category IV	Category V	Category III	Category IV
	0.40	0.50	0.50	0.40	0.50	0.50	0.50	0.50
	3.00	3.50	3.50	3.00	3.50	3.50	3.50	3.50
	7.50	8.50	9.50	7.50	8.50	9.50	8.50	9.50
Operating Temperature								
0°C~40°C								
Dimensions								
450×250×355mm								
Weight								
13.5 Kg								
14.7 Kg								